



12.1" Open Frame Touch Panel PC

Model:EB-1210EM



Specification:

| | |
|-----------------------|--|
| O/S | Driver for Linux ,Windows |
| CPU | Intel Atom D2550, 1.86GHZ |
| Chipsets | Intel NM10 |
| RAM | 2GByte DDR3-1333 / 4GByte DDR3-1333 |
| Hard Drive | 16GByte / 32GByte / 64GByte / 128GByte mSATA SSD |
| Graphic | Intel GMA3000,640MHz |
| Audio | Realtek HD ALC 662 |
| LAN | Realtek RTL8111E, 2*10/100/1000MBit RJ45 Ports |
| USB | 8* USB 2.0 ports, 4 as external |
| External Ports | 4*USB 2.0 |
| | 2* COM-RS232 |
| | 1*RS485/422 |
| | 2*RJ45 |
| | VGA |
| | Audio-in/ Audio-out |
| | PS/2(Mouse Keyboard) |
| | LPT |
| | Power on/off |
| | DC-IN (screwable) |
| Internal port | 2*Sata 300MB/S (1*MSATA) |
| | 1*MiniPCI-E |
| | PCI |
| | SATA2 |
| | 4*COM |
| Power consumption | 20W |
| Input Voltage | 8V~36V DC-IN (Wide voltage) |
| Operating Temperature | ,-10℃ to +60℃ |
| Storage Temperature | ,-20℃ to +70℃ |
| Driver | Windows, Linux; |
| Display | 245.76x184.32mm |
| Aspect Ratio | 4:3 |
| Physical Resolution | 1024 (W)*768(H) |

| | |
|------------------------|-------------------------------------|
| Brightness | 420cd/m ² |
| Contrast Ratio | 550:1 |
| React time | 2ms/6ms |
| Viewing Angle | 80/80/60/80 (Typ.)(CR≥10) (L/R/U/D) |
| Touch Panel | 5 wire resistive touch |
| Touch Panel Driver | Windows, Linux, Marc |
| React time touch panel | <10 ms |
| Surface Hardness | 3H |
| Power Supply | AC100~240V,DC12V |
| Cooling System | Fanless |
| Front Panel | |
| Install | Embedded , VESA100 |
| Case | Stainless steel and Aluminum |
| Size(WxHxD) | 315x210.1x71.7mm |

| | |
|----------|---|
| Optional | <i>W-lan optional</i> |
| | <i>Saw touch panel</i> |
| | <i>Outside HDD</i> |
| | <i>Luminance(600cd/ m² , 1000cd/ m² ,)</i> |
| | <i>12V DC-IN</i> |
| | <i>Advanced RAM and SSD/HDD</i> |

Packing list:
1* CD Driver
1* PC User Menu
1* Power Adapter
1* Touch Pen

Dimensions

