



RESUN ELECTRONICS CO.,LTD.

www.lcdpanelpc.org

10.1 Inch Touch PC_IP67



Specification:

O/S	Linux / Windows
CPU	Intel® Celeron® Processor J1900 (2M Cache, up to 2.42 GHz)
Chipsets	Intel® Bay Trail SOC
RAM	4GByte DDR3L-1600
Hard Drive	32GB SSD
Graphic	Intel® HD Graphics (854 MHz)
Audio	Realtek HD ALC 662
LAN	Realtek RTL8111E
External Ports (IP67 terminal)	1*LAN
	1*USB2.0
	1*COM
	1*DC-12V
	1*Sata 300MB/S (1*MSATA)
Internal port	1*MiniPCI-E
Input Voltage	DC-12v
Operating Temperature	,-10℃ to +60℃
Driver	Windows, Linux;
Display(mm)	216.96x135.6
Aspect Ratio	16:10
Physical Resolution	1280 (W)*800(H)
Brightness	300 cd/m ²
Contrast Ratio	800:1
React time	2ms/6ms
Visual angle	85/85/85/85(L/R/U/D)
Touch Panel	Projected capacitive touch panel(10 point touch)
Touch Panel Driver	Windows, Linux,
React time touch panel	<10 ms
Surface Hardness	≥6H
Power Supply	AC100-240V,DC12V
Cooling System	Fanless
Protection grade	completely IP67
Install	VESA100x100mm
Case	Aluminum
Size(WxHxD)(mm)	270x186x50
Optional	W-lan optional
	Bluetooth 2.0
	Advanced RAM and SSD/HDD

Packing list:

1* CD Driver , 1* Power Adapter , 1*IP67 DC Cable , 1*IP67 USB Cable , 1*IP67 COM Cable, 1*IP67 LAN Cable